



To whom it may concern:

RectorSeal's Warranty statement for firestop is contingent upon actual storage conditions and proper installation.

If RectorSeal® firestop products are correctly installed in accordance with our stated Manufacturers instructions and according to the UL tested systems, our products comply with UL 1479 "Fire Tests of Through-Penetration Firestops" standard requirements for Environmental Exposure Tests. This test relates to the performance of firestop products as originally installed, and compares to the performance testing after exposure to extreme temperatures and high humidity for an extended period of time.

If properly stored, our products have a minimum shelf life of two years, subject to inspection with the exception of our silicone product which has a one year shelf life.

The Rectorseal Corporation, manufacturer of BioFiresheild® Fire Stop products, has always been concerned about the long-term performance of our products. We implemented a testing program prior to the UL 1479 requirement for "Fire Tests of Through-Penetration Firestops". We burned materials in our UL sanctioned fire test facility to measure the performance of RectorSeal® products after extended periods of time as in accordance with current standards. Some of the tested materials exceed 15 years in age. Assuming that the substrate area surrounding the actual penetration has not been damaged, we warrant that BioFiresheild® products will perform satisfactorily for the sustainable life of the building.

*Larry Kaiser*

Larry Kaiser  
Vice-President, Sales  
RectorSeal Corp.